SPECIFICATION SHEET JFW MODEL 50DB-038 DC BLOCK INNER ONLY

Description

JFW Industries, Inc. Phone: 317-887-1340 sales@jfwindustries.com www.jfwindustries.com

Frequency Range	10 MHz-40 GHz
Impedance	50 Ohms nominal
VSWR	1.45:1 maximum

Inner Only DC Block

Insertion Loss	0.20 dB typical @ 3 GHz
	0.32 dB typical @ 6 GHz
	0.38 dB typical @ 18 GHz
	0.44 dB typical @ 26.5 GHz
	0.60 dB typical @ 40 GHz
	0.75 dB maximum 10 MHz-40 GHz

Capacitance	Value	100nFd	nominal

DC	Breakdown	Voltage	200 Volts

\Box	Input	D	\sim	T-7 - 1		maximum
Кŀ	I mmi	$P \cap W \cap Y$		Walls	average	maximiim :
T /T	TIPUC	LOWCI	_	vva c c b	average	IIICAZZZIIICAIII

Physical	Size	See	outline	drawing	092-8085

* 2.9mm connectors are both electrically and mechanically compatible with all K, 3.5mm and SMA connectors.

ECR/ECN	# DATE	REV	APPR / DATE	ECR/ECN	# DATE	REV	APPR / DATE
9999	10/14/2002	А	SL 10/14/2002	29907	10/31/2019	D	BAC 10/31/2019
26501	04/01/2016	В	TRS 04/01/2016	30464	06/23/2020	E	BAC 06/23/2020
26756	06/20/2016	С	TRS 06/20/2016	30634	09/03/2020	F	BAC 09/03/2020

Page 1 of 1 JFW FORM E-7-F REV F