

SPECIFICATION SHEET

JFW MODEL 50HFFA-XXX-10/8SMA

FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-8.4 GHz
Impedance	50 Ohms nominal
Attenuation Values	1 through 40 dB (any 1 dB increment)
VSWR	1.35:1 maximum < 1.25:1 typical
Attenuation Accuracy	± 0.5 dB (1-6 dB) ± 0.6 dB (7-10 dB) ± 0.8 dB (11-20 dB) ± 1.0 dB (21-30 dB) ± 1.2 dB (31-40 dB)
RF Input Power (bi-directional)	10 Watts average @ +25°C (derate linearly to 0 Watts @ +125°C)
Peak Power	500 Watts (5 microsecond pulse, 0.1% duty cycle)
RF Connector	SMA male/female
Temperature Range	-55°C to +125°C
Physical Size	See outline drawing 092-10091

Example models numbers:

50HFFA-003-10/8SMA	3dB, SMA male/female
50HFFA-006-10/8SMA	6dB, SMA male/female
50HFFA-010-10/8SMA	10dB, SMA male/female
50HFFA-020-10/8SMA	20dB, SMA male/female

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	12/10/2024		TRS 12/10/2024				