

**SPECIFICATION SHEET**

**JFW MODEL 50S-2161**

**1P4T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range 20-8400 MHz

Configuration 1P4T Self Terminating

Impedance 50 Ohms nominal

VSWR 1.30:1 typical 20-4000 MHz  
1.50:1 typical 4000-8400 MHz  
1.80:1 maximum 20-8400 MHz

Insertion Loss 1.4 dB typical @ 20 MHz  
1.8 dB typical @ 2000 MHz  
2.2 dB typical @ 4000 MHz  
2.7 dB typical @ 6000 MHz  
3.9 dB typical @ 8400 MHz  
4.5 dB maximum 20-8400 MHz

Isolation 100 dB typical @ 20 MHz  
81 dB typical @ 2000 MHz  
72 dB typical @ 4000 MHz  
69 dB typical @ 6000 MHz  
57 dB typical @ 8400 MHz  
50 dB minimum 20-8400 MHz

Switching Speed 10 microseconds maximum  
7.0 microseconds typical (OFF-ON)  
0.3 microseconds typical (ON-OFF)

RF Input Power +26 dBm average (Hot Switchable)

Test Software The included JFW software allows control of multiple  
(Microsoft .NET 4.0+) USB devices.  
(Windows Vista or greater) JFW managed library available for  
development in user made applications.

DC Supply +5 Vdc @ 10 mA nominal

DC Connector USB MINI-B  
6' MINI-B Male to A Male Cable included

RF Connector SMA female

Operating Temperature Range -40°C to +85°C

Storage Temperature Range -55°C to +90°C

Physical Size See outline drawing 092-9889

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/03/2022		BAC 11/03/2022				
32710	07/18/2023	A	BAC 07/18/2023				