

SPECIFICATION SHEET

JFW MODEL 50T-735

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-12.4 GHz

Impedance 50 Ohms nominal

VSWR 1.5:1 maximum
< 1.3:1 typical

RF Input Power 100 Watts average @ +25°C
Derate to 0 Watt @ +125°C

Peak Power 1000 Watts
(5 microsecond pulse, 1% duty cycle)

RF Connector N or SMA
(male or female)

Temperature Range -55°C to +125°C

Optional Mounting Bracket Add "-MBK" to end of model number if you want the optional mounting brackets included

Outline Drawing Numbers 092-10189-01 (N male)
092-10189-02 (N male with mounting brackets)
092-10189-03 (N female)
092-10189-04 (N female with mounting brackets)

Example model numbers:

50T-735 N M (N male)
50T-735 N F (N female)
50T-735 N M-MBK (N male with optional mounting brackets)
50T-735 N F-MBK (N female with optional mounting brackets)

50T-735 SMA M (SMA male)
50T-735 SMA F (SMA female)
50T-735 SMA M-MBK (SMA male with optional mounting brackets)
50T-735 SMA F-MBK (SMA female with optional mounting brackets)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/17/2024		TRS 07/17/2024				